

DOWNLINK BROADCASTING BY SEQUENTIAL TRANSMISSIONS FROM A COMMUNICATION STATION HAVING AN ANTENNA ARRAY

Bibliographic data	Description	Claims	INPADOC legal status
Publication number:	JP2002503048 (T)		Also published as:
Publication date:	2002-01-29		WO9940648 (A1)
Inventor(s):			EP1055267 (A1)
Applicant(s):	ARRAYCOMM, INC.		CN1289466 (A)
Classification:			CN100401829 (C)
- international:	H01Q1/24; H01Q3/26; H04B1/04; H04B7/06; H04B7/10; H04B7/26; H04W16/28; H01Q1/24; H01Q3/26; H04B1/04; H04B7/02; H04B7/04; H04B7/26; H04W16/00; (IPC1-7): H04B7/26; H01Q3/26; H04B1/04; H04B7/06; H04B7/10		AU2571999 (A)
- European:	H04W16/28; H01Q1/24A3; H01Q3/26; H04Q7/36B		
Application number:	JP20000530959T 19990203		
Priority number(s):	US19980020619 19980209; WO1999US02108 19990203		

[View INPADOC patent family](#)

[View list of citing documents](#)

[Report a data error here](#)

Abstract not available for JP 2002503048 (T)

Abstract of corresponding document: **WO 9940648 (A1)**

This invention relates to a method and apparatus for transmitting a downlink signal (103) from a communication station to one or more subscriber units to achieve a desired radiation level over a desired sector (e.g., everywhere), the communication station including an array of antenna elements (109.1-109.M) and one or more signal processors (105) programmed (in the case of programmable signal processors) to weight the downlink signal according to one of a sequence of complex valued weight vectors. The method includes sequentially repeating transmitting the downlink signal, each repetition with a different weight vector from the sequence until all weight vectors in the sequence have been transmitted with. The sequence is designed for achieving the desired radiation level during at least one of the repetitions. In this way, every user in the desired region is transmitted to in the time period.

Data supplied from the **esp@cenet** database — Worldwide